

Husqvarna LC 151S

Husqvarna LC 151 is an easy-to-use self-propelled lawnmower with collection, Bioclip® (mulch) and side discharge option, perfectly suited for medium to large sized lawns. The robust 51 cm steel cutting deck and the reliable and easy-start Husqvarna engine are built to tackle difficult mowing with great cutting results, while the ergonomically handle bar with soft grip offers a less-straining mowing experience. Easy foldable handlebar, convenient bail design and easy-adjust cutting height make every mow simpler. Collect blade leaves less clippings on the lawn for a tidy, professional look. Husqvarna LC 151 is an easy-to-use self-propelled lawnmower with collection, Bioclip® (mulch) and side discharge option, perfectly suited for medium to large sized lawns. The robust 51 cm steel cutting deck and the reliable and easy-start Husqvarna engine are built to tackle difficult mowing with great cutting results, while the ergonomically handle bar with soft grip offers a less-straining mowing experience. Easy foldable handlebar, convenient bail design and easy-adjust cutting height make every mow simpler. Collect blade leaves less clippings on the lawn for a tidy, professional look.



Easy adjustable handleQuick and easy adjustment of the handle in two different heights.



Ergonomic handle
Ergonomic angle of the handle in combination with easy to reach bail arms makes operation easy.

3-in-1 cutting system

This lawnmower offers versatility through several cutting options. Choose the cutting mode you require to achieve optimal results; collection for a tidy lawn, BioClip® (mulching) for lawn fertilization and side discharge for less frequently cut areas.



Easy grip for lifting in the frontEasy grip for lifting into storage, the car or carrying up stairs.



FEATURES

- Collection, BioClip® and side discharge
- Ergonomic handle
- Easy adjustable handle

- Easy grip for lifting in the front
- Central cutting height adjustment
- Easily foldable handle bar to facilitate transport and storage

| Technical Specifications | |
|---|--------------------------------|
| BATTERY | |
| Battery capacity | 0 Ah |
| Battery type | |
| CAPACITY | |
| Net power at preset rpm | 2800 rpm |
| Power output | 2.7 kW |
| Power rating | 2700 W |
| DIMENSIONS | |
| Article gross weight | 38700 g |
| Article net weight | 34800 g |
| Collector volume Cutting width | 65 l 51 cm |
| Cylinder displacement | 166 cm ³ |
| Handle height adjustment | 2 Step |
| Weight | 32.3 kg |
| Wheel size, Front | 203 mm |
| Wheel size, Rear | 203 mm |
| Wheelbase | 66 cm |
| ENGINE | |
| Cylinder displacement | 166 cm ³ |
| Electrode gap | 0.75 mm |
| Engine brand Engine cooling | Husqvarna Air |
| Engine cooling Engine name | HS 166A |
| | Husqvarna HQT-7 |
| Fuel tank volume | 11 |
| EQUIPMENT | |
| Air filter type | Paper |
| Ball beared wheels | Yes |
| BioClip® kit | Available as accessory |
| BioClip® plug Blade brake clutch (BBC) | Not included No |
| Blade type | Collect |
| Collector | Included |
| Collector type | Fabric with dust blocker |
| Collector volume | 651 |
| | No |
| Deflector Prive control | Included Reil orm |
| Drive control Drive system | Bail arm Self-propelled |
| Drive wheels | Rear |
| Foldable handle | Yes |
| Handle type | Ergonomic Handle (Bag Through) |
| Lawnmower drive type | Self-propelled |
| Side adjustable handle | No |
| Soft grip Theatte control | Yes |
| Throttle control Water hose connection | No No |
| Wheel bearing, front/rear | Yes/Yes |
| | Not applicable |
| LUBRICANTS | |
| Engine lubrication type | Splash |
| Fuel consumption | 407 g/kWh |
| Fuel consumption | 0.0233 I/min |
| Oil filter | None |
| Power/fuel type | Gasoline |
| MATERIALS Cutting deals and right | Charl |
| Cutting deck material Master pack: Paper + Cardboard | Steel 0 g |
| Master pack: Paper + Cardooard Metal total | 5 g |
| Paper + Cardboard total | 3950 g |
| PE total | 20 g |
| PET total | Og |
| Plastic foil | 31 g |
| Plastic rigid Plastic rigid | 0 g |
| Plastic total PS /EDS /LIDS total | 31 g |
| PS/EPS/HIPS total Rims, material | 0 g Plastic |
| SOUND AND NOISE | |
| Sound power level, guaranteed (LWA) | 98 dB(A) |
| Country points, 10101, guardinoon (Entry | 55 55(··) |
| | |

| Sound power level, measured | 96 dB(A) |
|---------------------------------------|----------------------|
| Sound pressure level at operators ear | 86 dB(A) |
| VIBRATIONS | |
| Vibrations handlebar | 8.5 m/s ² |
| PACKAGING | |
| Packaging height | 450 mm |
| Packaging length | 1040 mm |
| Packaging volume | 267 dm³ |
| Packaging width | 570 mm |
| Quantity in Master pack | 1 |